

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.08.2022

Version number 2

Revision: 05.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: 70GH407041 Additivo Antisediment**
- **MSDS no.** 194,357
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Application of the substance / the mixture** Printing inks
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Hubergroup Italia S.p.A.
Via A. Meucci No. 5/6/7
36050 Bolzano Vicentino
*Dystrybutor:
MICHAEL HUBER POLSKA SP.Z O.O.
Nowa Wieś Wrocławska ul.Nowa 21
55-080 Kąty Wrocławskie
Telefon:071 3548110, Fax: 0713548121
- **Informing department:**
Product Safety hubergroup
Telefon: + 49 89-9003-220
Telefax: + 49 89-9003-500
E-mail: product-safety@hubergroup.com
- **EMERGENCY CONTACT:**
phone: 0049 / 621 / 60 43 333
fax 0049 / 621 / 60 92 664
- **1.4 Emergency telephone number:**
During general business hours: Product Safety Division, Extension 220 or 375
- **Poisons Centre** Poisons Centre of Ireland: [+353 (0)1 809 2166]

Telefon: +39 0444-250000

Telefax: +39 0444-350324

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

—IE—

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.08.2022

Version number 2

Revision: 05.08.2022

Trade name: **70GH407041 Additivo Antisediment**

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07

· Signal word Danger

· Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P280 Wear protective gloves / eye protection / face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards This information is provided by the present Material Safety Data Sheet.

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Dangerous components:

CAS: 64-17-5	ethanol	80-100%
EINECS: 200-578-6	Flam. Liq. 2, H225; Eye Irrit. 2, H319	
Reg.nr.: 01-2119457610-43-xxxx		

CAS: 141-78-6	Ethyl acetate	1-2.5%
EINECS: 205-500-4	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	
Reg.nr.: 01-2119475103-46-xxxx		

· Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information

In all cases of doubt, or when symptoms persist, seek medical advice.

In case of unconsciousness place person in the recovery position. Never give anything by mouth.

· After inhalation

Remove to fresh air.

Keep patient warm and at rest.

(Contd. on page 3)

IE —

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.08.2022

Version number 2

Revision: 05.08.2022

Trade name: 70GH407041 Additivo Antisediment

(Contd. of page 2)

- **After skin contact**
Remove contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- **After eye contact**
Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Remove contact lenses. Obtain medical attention.
- **After swallowing** Do NOT induce vomiting. Obtain medical attention.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Alcohol resistant foam, CO₂, powders, water spray.
- **For safety reasons unsuitable extinguishing agents** Water jet.
- **5.2 Special hazards arising from the substance or mixture**
Appropriate breathing apparatus may be required.
Cool closed containers exposed to fire with water.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.
- **Additional information** Collect run-off from fire fighting.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Exclude sources of ignition.
Ventilate the area.
- **6.2 Environmental precautions:**
Do not allow to enter drains. If the product contaminates rivers and lakes or sewers inform respective authorities.
- **6.3 Methods and material for containment and cleaning up:**
Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local regulations. Clean preferably with a detergent. Avoid use of solvents.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Prevent the creation of flammable or explosive concentrations of vapour and avoid vapour concentrations higher than the occupational exposure limits.
Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded.

(Contd. on page 4)

— IE —

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.08.2022

Version number 2

Revision: 05.08.2022

Trade name: 70GH407041 Additivo Antisediment

(Contd. of page 3)

When transferring from one container to another apply earthing measures and use conductive hose material. Exercise caution when opening to allow pressure release. Printing ink removed from printing press for storage must be kept in the original container.

No sparking tools should be used.

Avoid inhalation of vapour. Smoking, eating and drinking should be prohibited in application area. For personal protection see Section 8. Comply with health and safety at work laws. Avoid concentrations higher than the occupational exposure limits (see Section 8), if applicable.

· **Information about protection against explosions and fires:**

Vapours may form explosive mixtures with air.

Solvent vapors are heavier than air and may spread along floors.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and containers:**

Storage rooms in which filling operations take place must have a conducting floor.

Never use pressure to empty: container is not a pressure vessel. Keep container tightly closed. Prevent unauthorized access. Opened containers must be carefully resealed and kept upright to prevent leakage.

Keep container tightly closed. No smoking.

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

· **Further information about storage conditions:**

Always keep in containers of the same material as the original one. Store in a dry, well ventilated place. Keep away from heat and direct sunlight. Store in accordance with the particular national regulations concerning water pollution.

Keep away from sources of ignition.

Note Instructions on the label.

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Additional information about design of technical systems:**

If relevant apply technical measures to comply with the occupational exposure limits. This can be by a good general extraction and-if practically feasible, be achieved by local exhaust ventilation.

· **Components with critical values that require monitoring at the workplace:**

Numerical data - if specified - are taken from the valid national lists.

141-78-6 Ethyl acetate (1-2.5%)

OEL Short-term value: 1468 mg/m³, 400 ppm

Long-term value: 734 mg/m³, 200 ppm

IOELV

· **DNELs**

64-17-5 ethanol

Dermal DNEL workers 343 mg/kg bw/d (human) (chronic, systemic)

Inhalative DNEL workers 950 mg/m³ (human) (chronic, systemic)

141-78-6 Ethyl acetate

Dermal DNEL workers 63 mg/kg bw/d (human)

Inhalative DNEL workers 734 mg/m³ (human)

(Contd. on page 5)

— IE —

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.08.2022

Version number 2

Revision: 05.08.2022

Trade name: 70GH407041 Additivo Antisediment

(Contd. of page 4)

· PNECs

64-17-5 ethanol

PNEC 0.63 mg/kg (soil)

PNEC STP 580 mg/l (STP)

141-78-6 Ethyl acetate

PNEC 0.22 mg/kg (soil)

PNEC STP 650 mg/l (STP)

· 8.2 Exposure controls

· Personal protective equipment

· Breathing equipment:

The use of respiratory protective measures, such as masks with filters for organic Vapours and dusts / mists are, in the absence of appropriate technical equipment, necessary for the protection of the employee. If exposure is above the exposure limit, then an appropriate, approved respirator must be worn. Please refer to the appropriate EU standard 14387.

· Protection of hands:

For prolonged or repeated contact use gloves.

Barrier creams may help to protect exposed skin, they should however not be applied once have come into contact with the product.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Applicable for example are gloves of KCL GmbH, D 36124 Eichenzell, e-mail: vertrieb@kcl.de with following specification (Laboratory test according EN 374)

Recommended protective glove:

Article / Name /Material / Thickness Material / Breakthrough Time Remarks

Nr. 898/ Butoject / Butyl / 0,7 mm Level 6 > 480 min. by fullcontact.

Nr. 890/ Vitoject / Viton / 0,7 mm Level 2 > 30 min. by splash contact

This recommendation is only for the product delivered by us and its intended purpose.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Use safety eyewear designed to protect against splash of liquids.

· Body protection:

Working clothes must not consist of textiles which show a dangerous melting behaviour in case of fire.

All parts of the skin should be washed after contact.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:

liquid

Colour:

according to the tradename of the product

· Smell:

characteristic

· Odour threshold:

Not determined.

· pH-value:

Not determined.

(Contd. on page 6)

— IE —

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.08.2022

Version number 2

Revision: 05.08.2022

Trade name: 70GH407041 Additivo Antisediment

(Contd. of page 5)

- **Change in condition**
 - Melting point/freezing point:** not determined
- **Flash point:** 12 °C
- **Inflammability (solid, gaseous)** Highly flammable.
- **Ignition temperature (Main Solvent):** 425 °C
- **Decomposition temperature:** Not determined.
- **Self-inflammability:** Not determined.
- **Explosive properties:** Not determined.
- **Critical values for explosion:**
 - Lower: approx.** 3.5 Vol %
 - Upper: approx.** 15.0 Vol %
- **Vapour pressure:** Not determined.
- **Density at 20 °C** 0.8679 g/cm³
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with**
 - Water:** Solvent fully miscible with water
- **Partition coefficient: n-octanol/water:** Not determined.
- **Viscosity:**
 - dynamic:** Not determined.
 - kinematic:** Not determined.
- **Solvent separation test**
 - Organic solvents:** 80-100 %
- **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability** No further relevant information available.
- **10.3 Thermal decomposition / conditions to be avoided:**
Stable under recommended storage and handling conditions (see section 7).
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:**
Keep well away from oxidising agents and strongly alkaline or strongly acid materials in order to avoid exothermic reactions.
- **10.6 Hazardous decomposition products:**
Exposition to high temperatures may produce hazardous decomposition products such as: carbon dioxide, carbon monoxide and smoke.

SECTION 11: Toxicological information

The mixture has been assessed following the additivity method of the CLP Regulation (EC) No 1272/2008 and/or GHS -Regulation and classified for toxicological hazards accordingly. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in skin dryness. The product may be

(Contd. on page 7)

— IE —

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.08.2022

Version number 2

Revision: 05.08.2022

Trade name: **70GH407041 Additivo Antisediment**

(Contd. of page 6)

absorbed through the skin.

· 11.1 Information on toxicological effects

· **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

64-17-5 ethanol

Oral LD50 7,060 mg/kg (rat)

Dermal LD50 20,000 mg/kg (rabbit) (10h)

Inhalative LC50 20,000 mg/m³ (rat)

141-78-6 Ethyl acetate

Oral LD50 5,620 mg/kg (rbt)

Dermal LD50 >18,000 mg/kg (rabbit)

Inhalative LC50 56,000 mg/m³ (rat) (4h)

· **Specific symptoms in biological assay:**

· **Skin corrosion/irritation** Based on available data, the classification criteria are not met.

· **Serious eye damage/irritation**

Causes serious eye irritation.

· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

· **Additional toxicological information:**

· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

· **Carcinogenicity** Based on available data, the classification criteria are not met.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

· **STOT-single exposure** Based on available data, the classification criteria are not met.

· **STOT-repeated exposure** Based on available data, the classification criteria are not met.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

The Product should not be allowed to enter drains of water courses or soil.

· 12.1 Toxicity

· **Aquatic toxicity:**

64-17-5 ethanol

Fish toxicity 13,000 mg/l (fish) (CL 50; 96h)

Daphnia toxicity 12.34 mg/l (daphnia) (EC50, 48h)

Algae toxicity 275 mg/l (algae) (EC50 72h)

141-78-6 Ethyl acetate

Fish toxicity 230 mg/l (fish) (LC 50; 96h)

Daphnia toxicity 717 mg/l (daphnia) (EC50; 48h)

Algae toxicity 5,600 mg/l (algae) (EC50; 48h)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

(Contd. on page 8)

— IE —

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.08.2022

Version number 2

Revision: 05.08.2022

Trade name: **70GH407041 Additivo Antisediment**

(Contd. of page 7)

- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Do not allow to enter drains.
- **European waste catalogue** 08 03 12: waste ink containing dangerous substances
- **Uncleaned packagings:** Waste
- **Recommendation:**
Emptied containers should be disposed off into scrap recycling or reconditioning respectively.
Not orderly emptied cans and ink remnants are special waste.

SECTION 14: Transport information

Transport only in accordance with ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport.

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1210
- **14.2 UN proper shipping name**
- **ADR** 1210 PRINTING INK
- **IMDG, IATA** PRINTING INK
- **14.3 Transport hazard class(es)**
- **ADR**



- **Class** 3 (F1) Flammable liquids.
- **Label** 3

- **IMDG, IATA**



- **Class** 3 Flammable liquids.
- **Label** 3
- **14.4 Packing group**
- **ADR, IMDG, IATA** II
- **14.5 Environmental hazards:**
- **Marine pollutant:** No
- **14.6 Special precautions for user** Warning: Flammable liquids.
- **Kemler Number:** 33
- **EMS Number:** F-E,S-D
- **Stowage Category** B

(Contd. on page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.08.2022

Version number 2

Revision: 05.08.2022

Trade name: **70GH407041 Additivo Antisediment**

(Contd. of page 8)

- **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.

- **Transport/Additional information:**

- **ADR**
- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
- **Transport category** 2
- **Tunnel restriction code** D/E

- **IMDG**
- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
- **UN "Model Regulation":** UN 1210 PRINTING INK, 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**
None of the ingredients is listed.
- **REGULATION (EU) 2019/1148**
- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**
None of the ingredients is listed.
- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**
None of the ingredients is listed.
- **Regulation (EC) No 273/2004 on drug precursors**
None of the ingredients is listed.
- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**
None of the ingredients is listed.
- **National regulations**
The product is subject to classification in accordance with the prevailing version of the regulations on hazardous materials.
- **Information about limitation of use:**
- **VOC-Content (EU):** 85.00 %

(Contd. on page 10)

— IE —

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.08.2022

Version number 2

Revision: 05.08.2022

Trade name: 70GH407041 Additivo Antisediment

(Contd. of page 9)

- **Other regulations, limitations and prohibitive regulations**
- **Swiss VOC-Regulation** 85.00 %
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

The information on this Safety Data Sheet is based on the present state of our knowledge and on current GHS Regulation and national laws. The user's working conditions are beyond our knowledge and control. It is always the responsibility of the user to take all necessary steps in order to fulfil the demands laid down in the local rules and legislation. The information in this Safety Data Sheet is meant as a description of the safety requirements of our product: it is not to be considered as a guarantee of the product's properties.

- **Relevant phrases**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

- *** Data compared to the previous version altered.**

— IE —